

Integration **IBUS 2.1**



Flat subwoofer enclosure with 2-channel amplifier A real 2.1 system

- Flat Subwoofer 20 cm (8") amplified at 75W RMS
Powerful, dynamic and tight bass

- Compact aluminum casing
Slim, good heat dissipation, robust

- 2-channel amplifier
2x55W RMS
Enables amplification of 2 front speakers,
and allows you to keep your original car radio

- Low-level and high-level inputs.
Connection to outputs on car radio loudspeakers
or via RCA cable.



- Remote control
Keep the control



Plug & Play cables provided

Power cable



ADVANTAGES

- ISO Plug & Play cable provided
[direct connection to ISO head unit]
- Easy installation under car seat [takes up little space]
- Intensifies the bass of your audio system
- Powerful amplification solution [allowing you to keep
the ergonomics of your original source without
losing display or control functions]
- Recreate a high-performance 2.1 system in your car

TECHNICAL SPECIFICATIONS

Type: Flat active subwoofer enclosure (20cm/8")

+ 2-channel amplifier

Subwoofer power: 150W max / 75W RMS

Subwoofer frequency response: 45Hz - 150Hz

2-channel amplifier power: 2x110W Max / 2x55W RMS

2-channel amplifier frequency response: 55Hz - 55KHz

Impedance: 4 Ohms (Warning: not stable under 2 Ohms
so not to be installed in parallel with a second kit)

Cable power: Directly from battery thanks to the power cable
5m x 3.30mm² (included)

Signal cable: ISO Plug & Play cable: 3m (included)

SNR > 80dBA - THD < 0.08 %

Height: 71.5mm (2.8") - **Length:** 344mm (13.5") - **Width:** 250mm (9.8")